

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 March 2005 (24.03.2005)

PCT

(10) International Publication Number  
**WO 2005/025657 A1**

(51) International Patent Classification<sup>7</sup>: **A61M 15/00**,  
15/08, 5/00, 16/00, A62B 18/02, 18/08

(21) International Application Number:  
PCT/US2004/029460

(22) International Filing Date:  
10 September 2004 (10.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10/658,769 10 September 2003 (10.09.2003) US  
10/876,480 28 June 2004 (28.06.2004) US

(71) Applicant (for all designated States except US): IN-  
NOMED TECHNOLOGIES, INC. [—/US]; 23257 State  
Road 7, Suite 206-207, Boca Raton, FL 33428 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **WOOD, Thomas, J.** [US/US]; 6632 Yomans Chapel Rd., Blackshear, GA 31516 (US). **HERNANDEZ, Shara** [US/US]; 6855 Pinehurst Drive, Miami, FL 33015 (US). **SHER, Bruce, M.** [US/US]; 3721 NE 28th Avenue, Lighthouse Point, FL 33064 (US).

(74) Agent: **MAIER, Timothy, J.**; PO Box 1817, Alexandria, VA 22313 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

[Continued on next page]

(54) Title: NASAL INTERFACE AND SYSTEM INCLUDING VENTILATION INSERTS



(57) Abstract: A ventilation or CPAP interface system (100) adapted to be inserted into a nares of a user to secure the interface is disclosed. A cannula (300) adapted to be connected to a source of ventilation gas forms a first portion of an input gas flow passage to supply the ventilation gas to the user. A nasal insert adapted to be inserted into the nares of the users forms a second portion of the input gas flow passage from the cannula (300) to a distal end of the nasal insert. A seal portion adapted to engage a portion of the first naris is provided adjacent the distal end of the nasal insert. The ventilation interface system (100) may optionally include feed tubes, y-connector (703), tube holder, headgear (700) and a headgear flange (800).



TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

- as to the identity of the inventor (Rule 4.17(i)) for all designations
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ,

TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations of inventorship (Rule 4.17(iv)) for US only

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## NASAL INTERFACE AND SYSTEM INCLUDING VENTILATION INSERT

## CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a Continuation-in-Part of co-pending Application No.

5 10/658,769, filed on September 10, 2003, the entire contents of which are hereby incorporated by reference and for which priority is claimed under 35 U.S.C. §120.

[0002] This application is related in subject matter to U.S. patent no. 6,478,026, PCT Patent Application Number PCT/US03/24590, filed August 6, 2003, U.S. patent applications no. 10/610,594 filed July 2, 2003, 10/044,925 filed January 15, 2002,

10 10/096,795 filed March 14, 2002, and 10/392,959 filed March 21, 2003, all to Thomas J. Wood, the disclosures of which are incorporated by reference herein in their entirety.

## BACKGROUND OF THE INVENTION

## 15 1. FIELD OF THE INVENTION

[0003] Exemplary embodiments of the invention are directed to a ventilation interface, and more particularly to a ventilation interface including a cannula forming a first portion of an input gas flow passage and a nasal insert forming a second portion of the input gas flow passage, the first and second portions of the input gas flow  
20 passage disposed at an obtuse angle to one another.

## 2. DISCUSSION OF RELATED ART

[0004] Obstructive sleep apnea syndrome (commonly referred to as obstructive sleep apnea, sleep apnea syndrome, and/or sleep apnea) is a medical condition characterized  
25 by repeated, prolonged episodes of cessation of breathing during sleep. During a

period of wakefulness, the muscles of the upper part of the throat passage of an individual keep the passage open, thereby permitting an adequate amount of oxygen to flow into the lungs. During sleep, the throat passage is narrowed due to the relaxation of the muscles. In those individuals having a relatively normally sized throat passage, the narrowed throat passage remains open enough to continue to permit the adequate amount of oxygen to flow into the lungs. However, in those individuals having a relatively smaller sized throat passage, the narrowed throat passage prohibits the adequate amount of oxygen from flowing into the lungs. Additionally, one or more of a nasal obstruction, a relatively large tongue, and/or certain shapes of the palate and/or the jaw of the individual further prohibit the adequate amount of oxygen from flowing into the lungs.

[0005] The individual having the above-discussed conditions can stop breathing for one or more prolonged periods of time (e.g., each period of time being 10 seconds or more). The prolonged periods of time during which breathing is stopped, or apneas, are generally followed by sudden reflexive attempts to breathe. The reflexive attempts to breathe are generally accompanied by a change from a relatively deeper stage of sleep to a relatively lighter stage of sleep. As a result, the individual suffering from obstructive sleep apnea syndrome generally experiences fragmented sleep that is not restful. The fragmented sleep results in one or more of excessive and/or inappropriate daytime drowsiness, headache, weight gain or loss, limited attention span, memory loss, poor judgment, personality changes, lethargy, inability to maintain concentration, and/or depression.

[0006] Other medical conditions can also prevent individuals, including adults and infants, from receiving the adequate amount of oxygen into the lungs. For example, an infant who is born prematurely can have lungs that are not developed to an extent

necessary to receive the adequate amount of oxygen. Further, prior to, during, and/or subsequent to certain medical procedures and/or medical treatments, an individual can be unable to receive the adequate amount of oxygen.

[0007] Under these circumstances, it is known to use a ventilation interface to apply a  
5 positive pressure to the throat of the individual, thereby permitting the adequate amount of oxygen to flow into the lungs. In the known ventilation interface, oxygen and/or room air containing oxygen is delivered through the mouth and/or nose of the individual. Known types of positive pressure applied by the known ventilation interface include continuous positive airway pressure (CPAP) in which a positive  
10 pressure is maintained in the throat passage throughout a respiratory cycle, bilevel positive airway pressure (BiPAP) in which a relatively high positive pressure is maintained during inspiration and a relatively low positive pressure is maintained during expiration, and intermittent mechanical positive pressure ventilation (IPPV) in which a positive pressure is applied when apnea is sensed (i.e., the positive airway  
15 pressure is applied intermittently or non-continuously).

[0008] A known ventilation interface for the application of such positive pressures includes a conventional face mask that covers the nose and/or mouth, as well as a conventional pair of nasal pillows that are inserted into corresponding nares of the naris.

20 [0009] The conventional face mask requires a harness, such as a headband and/or other headgear components, to provide and maintain a required fluid or gas tight seal between the mask and the face of the individual. Additionally, the conventional tubing will collapse if it is bent around the ears with the flat side against the side of the users head. Thus, the use of such a conventional harness and tubing results in a  
25 number of disadvantages.

[0010] For example, because pressure must be applied between the required harness and the head of the individual to maintain the required seal, the harness is generally uncomfortable, particularly when sleeping. The applied pressure often results in undesirable irritation and sores caused by movement of the mask and harness during periods of both wakefulness and sleep. Further, the required seal is generally unable to be maintained when the mask and harness is moved. The mask also generally applies an undesirable pressure to the sinus area that is adjacent to the nose, causing the nasal sinus airways to narrow, thereby increasing a velocity of flow through the upper anatomical airways and decreasing lateral pressure against the nasal mucosal walls. Further, the tubing may fold undesirably further exacerbating the above problem. The above-discussed combination of increased flow velocity and decreased pressure results in the removal of moisture from the mucosal walls during inspiration, causing an undesirable drying and a burning sensation within the nares. As a result, the individual may remove the mask to alleviate these discomforts, consequently discontinuing the beneficial application of the positive pressure.

[0011] The conventional nasal pillows include pillowed style nasal seals that are pressed against the bottom portion of the nares. However, the known nasal pillows also require the use of a harness to keep the nasal pillows pressed against the bottom of the nares, resulting in disadvantages similar to those of the conventional face mask.

[0012] For these reasons, it is desirable to provide a nasal interface and system that overcomes one or more of the above-discussed disadvantages.

#### SUMMARY OF THE INVENTION

[0013] Exemplary embodiments of the present invention provide a ventilation interface adapted to be inserted into a nares of a user to secure the interface. A

cannula adapted to be connected to a source of ventilation gas forms a first portion of an input gas flow passage to supply the ventilation gas to the user. A nasal insert adapted to be inserted into the nares of the user forms a second portion of the input gas flow passage from the cannula to a distal end of the nasal insert. A seal portion adapted to engage a portion of the first nares can be provided adjacent the distal end of the nasal insert. The first and second portions of the input gas flow passage are disposed at an obtuse angle to one another.

[0014] In another exemplary embodiment of the invention, a gas output forms a portion of an output gas flow passage from the nasal insert to an exterior of the ventilation interface to channel a gas expired by the user. Optionally, the second portion of the input gas flow passage and the portion of the output gas flow passage can be configured to provide laminar flow therebetween.

[0015] In yet another exemplary embodiment, the seal portion of the nasal insert forms a seal with the naris of the user by optionally a resiliency of the seal portion of the nasal insert or a resiliency of the nares of the user or some combination of the two. Further, at least one of the nasal insert and the seal portion may, optionally, be sufficiently flexible to be expanded by a positive pressure provided by the ventilation gas to help form a seal portion.

[0016] Exemplary embodiments of the present invention further provide a ventilation interface adapted to be inserted into a nares of a user which can secure the interface. A first subassembly forms a first portion of an input gas flow passage from a ventilation gas supply source. A second subassembly forms a second portion of the input gas flow passage from the first subassembly to a first naris of the nares of the user. A subassembly for engaging a portion of the first naris is provided on the

second subassembly. The first and second portions of the input gas flow passage are disposed at an obtuse angle to one another.

[0017] Exemplary embodiments of the present invention further provide a feed tube and y-connector adapted for use in a ventilation interface system. The feed tube  
5 having an annular sleeve and may optionally include a first exterior portion and a second exterior portion; the first exterior portion including a plurality of first ribs and a second exterior portion including a plurality of second ribs.

[0018] Yet further exemplary embodiments of the present invention provide a ventilation interface system including a cannula adapted to be connected to a source  
10 of ventilation gas via a feed tube and a y-connector, the cannula forming a first portion of an input gas flow passage to supply the ventilation gas to the user. A nasal insert adapted to be inserted the nares of the user, the nasal insert forming a second portion of the input gas flow passage from the cannula to a distal end of the nasal insert. A seal portion adapted to engage at least a portion of the nares of the user, the  
15 seal portion provided adjacent the distal end of the nasal insert wherein the first and second portions of the input gas flow passage are disposed at an obtuse angle to one another. Optionally, head or harness gear may be provided to assist in holding the nasal inserts in place.

[0019] In another exemplary embodiment, the headgear's interaction with the  
20 headgear flange may hold the nasal inserts in the nares of a user. Further, a thin skirt may optionally be wrapped around the ridges of the nasal insert and may assist in preventing leaks.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0020] A more complete appreciation of the exemplary embodiments of the present  
25 invention, and one or more of the attendant advantages thereof, will be readily



ascertained and/or obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, wherein:

- [0021] Figure 1 shows an exploded side elevation view of a first exemplary  
5 embodiment of the ventilation interface system.
- [0022] Figure 2 shows a side elevation view of a ventilation insert.
- [0023] Figure 3 shows a side view of the ventilation insert of Figure 2.
- [0024] Figure 4 shows a top view of the ventilation insert of Figure 2.
- [0025] Figure 5 shows a side view of the ventilation insert of Figure 2.
- 10 [0026] Figure 6 shows a cross-sectional view taken from line I-I in Figure 3.
- [0027] Figure 7 shows an elevated side view of an oval feed tube.
- [0028] Figure 8 shows a cross-sectional view of a feed tube taken along line II-II in Figure 7.
- [0029] Figure 9 shows a cross-sectional view of the oval feed tube of Figure 7.
- 15 [0030] Figure 10 shows a side view of a round feed tube.
- [0031] Figure 11 shows a cross-section of the round feed tube of Figure 10.
- [0032] Figure 12 shows a cross-sectional view of the round feed tube of figure 9.
- [0033] Figure 13 shows a side elevation view of an exemplary embodiment of a ventilation insert.
- 20 [0034] Figure 14 shows a side view of the ventilation insert of Figure 13
- [0035] Figure 15 shows a side view of the ventilation insert of Figure 13.
- [0036] Figure 16 shows a top view of the ventilation insert of Figure 13
- [0037] Figure 17 shows a bottom view of the ventilation insert of Figure 13
- [0038] Figure 18 shows a cross sectional view along the line IV-IV of Figure 13
- 25 [0039] Figure 19 shows a cross sectional view along the line V-V of Figure 16.

[0040] Figure 20 shows a cross sectional view along the line VI-VI of Figure 16.

#### DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

5 [0041] Examples of one or more exemplary embodiments of the present invention will now be described with reference to the drawings, wherein like reference numbers throughout the several views identify like and/or similar elements.

[0042] Generally referring to Figures 1-20, exemplary embodiments of the present invention can provide a ventilation interface system adapted to be inserted into a nares  
10 of a user to secure the interface. A cannula 300 adaptable to be connected to a source of ventilation gas (not shown) forms a first portion 141 of an input gas flow passage to supply the ventilation gas to the user. Nasal inserts 120 are adapted to be inserted into the nares of the user forms a second portion 123 of the input gas flow passage from the cannula to a distal end of the nasal insert 130. A seal portion 122 optionally  
15 adapted to engage a portion of the nares of the user is positioned at the distal end 130 of the nasal insert. The first 141 and second portions 123 of the input gas flow passage may be disposed at an obtuse angle to one another.

[0043] In another exemplary embodiment of the invention, the obtuse angle is between about 110° and about 170°, and more preferably the obtuse angle is about  
20 135°.

[0044] In a further exemplary embodiment of the invention, gas output flow passages 150, form a portion of an output gas flow passage from the nasal insert 120 to an exterior of the ventilation interface to channel a gas expired by the user. Optionally, the second portion 123 of the input gas flow passage formed by the nasal insert is  
25 about parallel with the portion of the output gas flow passage 150. Moreover, the

second portion 123 of the input gas flow passage and the portion of the output gas flow passage 150 are configured to, optionally, provide laminar flow therebetween.

[0045] In yet another exemplary embodiment, the nasal inserts 120, and the seal portions 122 form a seal with the nares of the user by, optionally, a resiliency of the seal portion 122 and nasal insert 120 or a resiliency of the nares of the user or some combination of the above with a headgear 700 assisting in gently holding the nasal insert 120 into the nares. Alternatively, the headgear 700 may be configured to be attached to headgear flange 800, 801. Further, at least one of the nasal inserts 120 and the seal portions 122 may, optionally, be sufficiently flexible to be expanded by a positive pressure provided by the ventilation gas to help form a seal with the nares of the user. Additionally, a skirt 180 may be attached to the portion 122 of the nasal insert 120 to prevent leakage.

[0046] Specifically, as shown in the figures 1-20 exemplary embodiments of a ventilation interface 100 of the present invention can include, among other components, a cannula 300, nasal inserts 120, seal portions 122 and gas outputs 150, to be described below.

[0047] The cannula 300 can be adapted to be connected to a source of ventilation gas (not shown), such as oxygen and/or room air containing oxygen, to apply a positive pressure to the throat of the user of the ventilation interface 100, thereby permitting an adequate amount of oxygen to flow into the lungs. Optionally, the system may be connected to a mechanical ventilator. Although the figures show certain exemplary embodiments of the cannula 300, it is to be understood that the cannula 300 can be of any type, so long as the cannula 300 can be connected to the source of the ventilation gas.

[0048] The cannula 300 can include a distal end 142 connectable to the source of the ventilation gas via a feed tube 500, 600. In an exemplary embodiment of the invention, the y-connector 703 can include an exterior surface and an interior surface defining a wall portion therebetween, each of the exterior and interior surfaces having optionally substantially circular or oval cross section. By this arrangement, the y-connector 703 can be connected with the source of the ventilation gas at one end and to the feed tube at the other end 500, 600.

[0049] The cannula 300 can include a cannula body 303 adjacent to distal end 142 that defines a first portion 141 of the input gas flow passage, and more specifically can define the second portion 123 of the input gas flow passage through the cannula body 303. The cannula body 303 can define a portion of an output gas flow passage, and, more specifically, can define the fourth portion 153 of the output gas flow passage from the nasal insert 120 through the cannula body 303 (discussed below). The cannula body 303 can extend along one or more axes such that laminar flow can be achieved within the second portion 123 of the input gas flow passage and/or such that laminar flow can be achieved within the fourth portion 153 of the output gas flow passage. Further, the cannula body 303 can extend along the one or more axes such that laminar flow can be achieved between the second portion 123 of the input gas flow passage and portions of the input gas flow passage upstream and/or downstream of the second portion, and/or can extend along the one or more axes such that laminar flow can be achieved between the fourth portions 153 and the second portions 123 of the output gas flow passage. Optionally, portions of the axes of the second portion 123 of the input gas flow passage and/or the fourth portion 153 of the output gas flow passage extend along a substantially arcuate line.

[0050] The nasal insert 120 can be disposed adjacent the cannula body 303 and can be adapted to be inserted the nares of the user to apply the positive pressure to the throat of the user. Although the figures show certain exemplary embodiments of the nasal insert 120, it is to be understood that the nasal insert 120 can be of any type, so long  
5 the nasal insert 120 can be inserted into the nares to apply the positive pressure.

[0051] The nasal insert 120 can define a third portion 305 and a fourth portion 153 of the input gas flow passage, and more specifically can define the third 305 and fourth 153 portions of the input gas flow passage from the cannula 300 through the nasal insert 120. The nasal insert 120 can define a second portion 123 and a third portion  
10 305 of the output gas flow passage, and more specifically can define the second 123 and third 305 portions of the output gas flow passage from the sealing portion 122 through the nasal insert 120. In an exemplary embodiment of the invention, the nasal insert 120 can include an exterior surface and an interior surface defining a wall portion therebetween, each of the exterior and interior surfaces may have a varying  
15 cross section including oval shapes or, optionally, substantially circular or flat shapes, such that the nasal inserts 120 can define the above-identified flow passages.

[0052] The nasal insert 120 can have a maximum interior cross sectional area and circumference at a proximal end 121 of the nasal insert 120 that is adjacent the cannula 300, thereby defining the third portion 305 of the input/output gas flow  
20 passage. The nasal insert 120 may optionally have a minimal interior cross sectional area and circumference at a distal end 130 of the nasal insert 120 that is disposed away from the cannula 300 (i.e., opposite the proximal end 121), thereby defining the fourth portion 153 of the input/output gas flow passage, and thereby defining the second portion 123 of the input/output gas flow passage. Optionally, the nasal insert  
25 120 may have the substantially same interior cross sectional area and circumference at

the distal 130 and proximal ends 121. In an exemplary embodiment of the invention, the proximal end 121 may, optionally, be in the form of an ellipse, oval or circle and the distal end 122 can be in the form of an ellipse, oval or circle.

[0053] The nasal insert 120 can extend along an axis such that laminar flow can be  
5 achieved within and/or between the third 305 and fourth portions 153 of the  
input/output gas flow passage, and/or within and/or between the second 123 and third  
305 portions of the output gas flow passage. Further, the nasal insert 120 can extend  
along the axis such that laminar flow can be achieved among the third 305 and fourth  
153 portions of the input/output gas flow passage and portions of the input gas flow  
10 passage upstream and/or downstream of the third 305 and fourth 153 portions, and/or  
such that laminar flow can be achieved among the second and third portions of the  
output gas flow passage and portions of the output gas flow passage upstream and/or  
downstream of the second 123 and third 305 portions.

[0054] The seal portion 122 can be disposed adjacent the distal end 130 of the nasal  
15 insert 120, and can be adapted to engage the interior portion of the user's nares to  
thereby retain the ventilation interface 100 therewithin. Although the figures show  
certain exemplary embodiments of the seal portion 122, it is to be understood that the  
seal portion 122 can be of any type, so long as the seal portion 122 can engage the  
interior portion of the nares.

20 [0055] In yet another exemplary embodiment of the invention, the seal portion 122  
can include an exterior surface and an interior surface defining a wall portion  
therebetween, each of the exterior and interior surfaces may have an about C-shaped  
or arcuate surface and having a circular or oval cross section, such that the seal  
portion 122 can define the above-identified flow passages. An interior portion of the  
25 seal portion 122 can have an interior cross section in the form of an ellipse, or

alternatively can have one or both of an interior surface and an exterior surface with an about tear-shaped or optionally a circular cross-section.

[0056] In another exemplary embodiment of the invention, the maximum interior cross section and its corresponding circumference may, optionally, be greater than the interior cross section and circumference of the distal end 130 of the nasal insert 120. A maximum exterior cross section and its corresponding circumference of the seal portion 122 may optionally be greater than the exterior cross section and circumference of the distal end 130.

[0057] The seal portion 122 and/or the nasal insert 120 can include an elastic material, the resiliency of which may retain the first ventilation interface 100 in the nares. Further, the seal portion 122 and/or the nasal insert 120 can optionally be expanded by the positive pressure of the ventilation gas, thereby aiding in the retention of the first ventilation interface 100 within the nares. Optionally, the nasal insert 120 need not deform when entering the user's nares.

[0058] The seal portion 122 can extend along an axis such that laminar flow can be achieved within the fifth portion 152 of the input gas flow passage, and/or within the first portion of the output gas flow passage. Further, the seal portion 122 can extend along the axis such that laminar flow can be achieved between the fifth 152 portion of the input gas flow passage and upstream of the input gas flow passage, and/or such that laminar flow can be achieved between the first 141 portion of the output gas flow passage and downstream of the output gas flow passage. Optionally, the axis is substantially a straight line.

[0059] The gas output 150 can be disposed adjacent the cannula body 303 opposite to the nasal insert 120, and can be adapted to channel the gas expired by the user to the exterior of the ventilation interface. Although the figures show certain exemplary

embodiments of the gas output 150, it is to be understood that the gas output 150 can be of any type, so long as the gas output 150 can channel the gas expired by the user to an exterior of the ventilation interface 100.

[0060] The gas output 150 can define a fifth portion 152 of the output gas flow passage, and more specifically can define the fifth 152 of the output gas flow passage from the cannula body 303 through the gas output. In an exemplary embodiment of the invention, the gas output 150 can include an exterior surface and an interior surface defining a wall portion therebetween, each of the exterior and interior surfaces having a varying cross section including circular shapes, such that the gas output 150 can define the above-identified flow passages. The gas output 150 can have a maximum interior cross sectional area and circumference at a proximal end 141 of the gas output 150 that is adjacent the cannula body 303, thereby defining the fifth 152 portion of the output gas flow passage. The gas output 150 can have a minimal interior cross sectional area and circumference at a distal end 157 of the gas output 150 that is disposed away from the cannula body 303 (i.e., opposite the proximal end 141), thereby defining the fifth 152 portion of the output gas flow passage.

[0061] In an exemplary embodiment, laminar flow is achieved among and/or within one or more of the portions (i.e., the first through fifth portions) of the input gas flow passage of the first ventilation interface 100 is achieved among and within all of the portions of the input gas flow passage.

[0062] Also as discussed above, the output gas flow passage can channel the expired gas from the nares of the user of the ventilation interface 100, and more specifically can channel the expired gas from of the nares of the user to and through the first portion of the sealing portion 122, to and through the third 305 portion of the distal end 122 of the nasal insert 120, to and through the second 123 portion of the proximal



end 121 of the nasal insert 120, to and through the fourth 153 portion of the cannula body 303 of the cannula 300, to and through the fifth 152 portion of the gas output 150, to the exterior of the ventilation interface 100. In an exemplary embodiment of the invention, laminar flow is achieved among and/or within each of the portions (i.e., the first through fifth portions) of the output gas flow passage of the ventilation interface 100, and more optionally is achieved among and within all the portions of the output gas flow passage.

[0063] A ventilation interface 100 according to exemplary embodiments of the present invention can avoid disadvantages of the known or conventional ventilation interface requiring a harness.

[0064] Referring generally to figures 7-12. In yet another exemplary embodiment of the present invention, the oval feed tubing 500 provides an oval cross-section 505. The distance 503 between the ribs 501 at the bottom surface shorten when bent and the distance between the ribs 504 on the top 502 surface of the tubing wall lengthens in order for the tubing to bend without decreasing the cross-sectional area of the tube. This also gives the oval tubing 500 the ability to drape around the ears of a user. Optionally, circular tubing 600, with a circular cross-sectional are 602, provides ribs 601 which can be bent around the ears.

[0065] In figure 9, the distance between the bottom ribs 503 are spaced when the tubing is straight. When draped in a radius position the distance between the lower ribs 503 is closed and the wall shortens without causing spring-back tension. The points between the top ribs 500 simply separate further at the top when the tube is bent, but not the bottom ribs 503 where the wall thickness is very thin. In between each point of the 500 area there is a slight bend of the thin wall. The accumulation of

the sum of each bend gives the radius at the top of the tubing. The accumulation of the compression of the spaces at 503 gives the tubing its radius at the bottom.

[0066] Thus, the ventilation interface system according to the exemplary embodiments of the present invention can provide the ventilation gas from the  
5 ventilation source to the nares at a lower velocity as compared to the conventional ventilation interface, thereby decreasing an amount of moisture removed from the mucosal walls. Further the ventilation interface system provides better comfort and functionality over the known conventional systems.

[0067] Generally referring to figures 13-20 the headgear 700 may be configured to be  
10 attached to headgear flange 800, 801. The interaction between the headgear 700 and the headgear flange 800, 801 may hold the nasal inserts in the nares of the user.

[0068] Numerous additional modifications and variations of the exemplary embodiments present invention are possible in light of the above teachings. It is therefore to be understood that within the scope of the appended claims, exemplary  
15 embodiments of the present invention may be practiced otherwise than as specifically described herein.

## WHAT IS CLAIMED IS:

1. A ventilation interface configured to be inserted into a nares of a user to secure the interface, comprising:
  - a cannula with at least one nasal insert and at least one exhaust port; the
  - 5 cannula forming a first portion of an input gas flow passage to supply the ventilation gas;
  - the nasal insert configured to be inserted into a first naris of the nares of the user, the nasal insert forming second and third portions of the input gas flow passage from the cannula to a distal end of the nasal insert;
  - 10 a seal portion configured to engage at least a portion of the nares, the seal portion being provided on the distal end of the at least one nasal insert; and
  - at least one headgear flange disposed the cannula body.
2. The ventilation interface according to claim 1, wherein the first, second and third portions of the inflow passage are disposed at an obtuse angle which is between
- 15 about 110° and about 170°.
3. The ventilation interface according to claim 1 wherein the headgear flange is configured to receive a headgear strap which holds the nasal insert in place.
4. The ventilation interface according to claim 1, wherein the proximal end of the nasal insert forms a second portion of the input gas flow passage having a
- 20 substantially oval cross section.
5. The ventilation interface according to claim 4, wherein a distal end of the nasal insert forms a third portion of the input gas flow passage having a substantially oval cross section.
6. The ventilation interface according to claim 5, wherein the third portion of

the input gas flow passage has a circumference that is less than a circumference of the second portion of the input gas flow passage.

7. The ventilation interface according to claim 6, wherein the seal portion forms a third portion of the input gas flow passage having a substantially oval cross section.

8. The ventilation interface according to claim 7, wherein the distal end of the nasal insert includes a first exterior portion having a substantially oval cross section.

9. The ventilation interface according to claim 8, wherein the portion of the nasal insert proximal the cannula includes a second exterior portion having a substantially oval cross section.

10. The ventilation interface according to claim 9, wherein the first exterior portion has a circumference that is less than a circumference of the second exterior portion.

11. The ventilation interface according to claim 10, wherein the seal portion includes a third exterior portion having at least one of a substantially oval cross section or a round cross section.

12. The ventilation interface according to claim 11, wherein the third exterior portion has a circumference that is larger than the circumference of the second exterior portion.

13. The ventilation interface according to claim 11, wherein the third exterior portion has a circumference that is substantially equal to the circumference of the second exterior portion.

14. The ventilation interface according to claim 1, further comprising:  
a gas output forming a portion of an output gas flow passage from the nasal insert to an exterior of the ventilation interface to channel a gas expired by the user.

15. The ventilation interface according to claim 14, wherein the second portion of the input gas flow passage formed by the nasal insert is about parallel with the portion of the output gas flow passage.

16. The ventilation interface according to claim 15, wherein the second  
5 portion of the input gas flow passage and the portion of the output gas flow passage are configured to provide laminar flow therebetween.

17. The ventilation interface according to claim 16, wherein a distal end of the gas output forms a first portion of the output gas flow passage having a substantially circular cross section.

10 18. The ventilation interface according to claim 17, wherein a portion of the gas output proximal the cannula forms a second portion of the output gas flow passage having a substantially circular cross section.

19. The ventilation interface according to claim 18, wherein the first portion of the output gas flow passage has a circumference that is less than a circumference of  
15 the second portion of the output gas flow passage.

20. The ventilation interface according to claim 1, wherein at least one of the nasal insert and the seal portion is sufficiently flexible to be expanded by a positive pressure provided by the ventilation gas.

21. The ventilation interface according to claim 1, wherein at least one of the  
20 nasal insert and the seal portion forms a seal with the nares of the user by at least one of deformation of at least one of the nasal insert, the nares of the user, the seal portion or a headgear.

22. The ventilation interface according to claim 1, wherein at least one of the nasal insert and the seal portion forms a seal with the nares of the user by friction

between the nares of the user and at least one of the nasal insert, the seal portion or a headgear.

23. The ventilation interface according to Claim 1, wherein at least one of the nasal inserts and the seal portion form a seal with at least one naris of the user by a  
5 resiliency of at least one of said seal portion and said nares of the user and a headgear.

24. A ventilation or CPAP interface system, comprising:

a cannula, nasal inserts, seal portions and exhaust ports;

feed tubes and a y-connector;

a tubing connector;

10 head gear and at least one headgear flange;


the cannula is adapted to be connected to a source of ventilation gas via the feed tubes and y-connector, the cannula forming a first portion of an input gas flow passage to supply the ventilation gas to the user;

the nasal inserts are adapted to be inserted into the nares of the user, the nasal  
15 inserts form a second portion of the input gas flow passage from the cannula to a distal end of the nasal inserts; and

a seal portion adapted to engage at least a portion of the nares, the seal portion provided adjacent a distal end of the nasal insert.

25. The ventilation interface according to claim 24, wherein the headgear  
20 flange is configured to receive a headgear strap which holds the nasal insert in place.

FIG. 1



2/8  
FIG. 2




FIG. 3




FIG. 4






FIG. 5





FIG. 6



4/8  
FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12



6/8

FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20



# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US04/29460

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : A61M 15/00, 15/08, 5/00, 16/00; A62B 18/02, 18/08

US CL : 128/200.24, 202.18, 203.22, 203.29, 204.12, 205.25, 206.12, 206.18, 206.21, 206.27, 206.28, 207.11

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
U.S. : Please See Continuation Sheet

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,477,852 A (LANDIS et al.) 26 December 1995, figures 1-4, 13A, 13B	1, 3-5, 14-18, 20-25
---		
Y		2, 6-13, 19

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

### \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T"

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X"

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y"

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&"

document member of the same patent family

Date of the actual completion of the international search

23 February 2005 (23.02.2005)

Date of mailing of the international search report

23 FEBRUARY 2005

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US

Commissioner for Patents

P.O. Box 1450

Alexandria, Virginia 22313-1450

Facsimile No. (703)305-3230

Authorized officer

DIANA L OLEKSA

Telephone No. 703-305-2357